

## Seicane T6015 2002-2008 Chrysler Dodge Jeep car radio aftermarket car stereo head unit upgrade installation replacement instruction

Seicane T6015 2002-2008 Chrysler Dodge Jeep car radio after installation



**Please note:**

**This unit can be suitable for the following cars which are also with the same installation steps as follows.**

- 2005-2007 Chrysler 300 Limited/Touring
- 2005-2007 Chrysler 300C (W/NAV)
- 2002-2005 Chrysler 300-M
- 2007-2008 Chrysler Aspen
- 2007-2008 Chrysler Aspen (W/NAV)
- 2002-2004 Chrysler Concorde
- 2004-2008 Chrysler Pacifica
- 2002-2010 Chrysler PT Cruiser
- 2002-2006 Chrysler Sebring
- 2002-2007 Chrysler Town & Country
- 2002-2003 Chrysler Voyager
- 2007-2008 Dodge Caliber
- 2006-2007 Dodge Caliber (W/Factory NAV)
- 2002-2007 Dodge Caravan

2006-2007 Dodge Charger (W/Factory NAV)  
2006-2007 Dodge Charger (W/O NAV)  
2002-2007 Dodge Dakota P/U  
2002-2003 Dodge Durango  
2004-2007 Dodge Durango (W/Factory NAV)  
2004-2007 Dodge Durango (W/O NAV)  
2002-2004 Dodge Intrepid  
2005-2007 Dodge Magnum (W/Factory NAV)  
2005-2007 Dodge Magnum (W/O NAV)  
2002-2005 Dodge Neon  
2002-2005 Dodge RAM Pickup  
2006-2008 Dodge RAM Pickup (W/Factory NAV)  
2006-2008 Dodge RAM Pickup (W/O NAV)  
2002-2003 Dodge RAM VAN (Fullsize)  
2002-2006 Dodge Stratus  
2002-2008 Dodge Viper  
2006-2007 Jeep Commander  
2006-2007 Jeep Commander (W/Factory NAV)  
2007-2008 Jeep Compass  
2007-2008 Jeep Compass (W/Factory NAV)  
2002-2007 Jeep Grand Cherokee  
2005-2007 Jeep Grand Cherokee (W/Factory NAV)  
2002-2007 Jeep Liberty  
2007 Jeep Patriot  
2003-2006 Jeep Wrangler  
2006-2007 Mitsubishi Raider  
2006-2007 Mitsubishi Raider (W/NAV)

**Some tips before the installation:**

1. Please disconnect the power before the installation.
2. Please prepare a lever and a screwdriver before the removal and the installation.
3. Please keep all the separate parts from the car. Please take great care of the dashboard to avoid scratching it during its detachment and installation. Please keep handy any parts from the car and make use of all the original screws from the car as much as possible. so each related part of the unit can be fixed securely.
4. For your convenience, here's the recommended tools for removal and installation from Seicane, please check for more details:

<http://www.seicane.com/car-dvd-dismantling-device-srd-400>

## 2002-2008 Chrysler Dodge Jeep car radio installation steps

1. Loosen the trim panel with a lever.



2. Take the panel off the dash and disconnect the wires from the car.



3. Remove the four screws which are holding the unit with a screwdriver.



4. Take out the unit and disconnect the wire harness at the back of the unit.



5. Check all the accessories for the new Seicane car radio.



6. Connect the Seicane car radio to your original car radio 's plugs.



7. Put the new Seicane car radio into the dash.

8. Turn on the new Seicane car radio to have a careful check if everything works well. If it doesn't, please check whether all the cables are connected correctly.

9. Put trim panel back on your new Seicane car radio after the normal test.

**Please note:**

We suggest you arrange a professional to install it. If you have any questions about installation, please send us photos about your original car's plugs, we can make a wiring diagram for your car.