

Seicane S127301 2000-2010 Ford Focus Mondeo aftermarket car stereo upgrade installation replacement instruction

Seicane S127301 2000-2010 Ford Focus Mondeo car radio after installation



Please note:

This unit can be suitable for the following cars which are also with the same installation steps as follows.

- 2000-2010 Ford Focus
- 2003-2007 Ford Mondeo
- 2007-2009 Ford S-MAX
- 2007-2009 Ford C-MAX
- 2005-2007 Ford Galaxy
- 2005 Ford Fiesta Form
- 2006-2011 Ford Fusion
- 2007-2009 Ford Connect

Here are some tips about the installation:

1. Please disconnect the power before the installation.
2. Please prepare a lever and a screwdriver before the removal and the installation.
3. Please keep all the separate parts from the car. Please take great care of the dashboard to avoid scratching it during its detachment and installation. Please keep handy any parts from the car and

make use of all the original screws from the car as much as possible. so each related part of the unit can be fixed securely.

4. For your convenience, here's the recommended tools for removal and installation from Seicane, please check for more details: <http://www.seicane.com/car-dvd-dismantling-device-srd-400>

2000-2010 Ford Focus car radio installation guide

Step 1: Remove the trim around gear shifter.



Step 2: Remove screws securing center console lid with a screwdriver.



Step 3: Remove the center console trim.



Step 4: Remove console side panels on both driver and passenger sides.



Step 5: Remove bolts securing radio bezel and AC controls.



Step 6: Unplug AC controls (from passenger side).



Step 7: Remove the radio bezel and AC controls.



Step 8: Remove screws securing radio to the vehicle.



Step 9: Take the original radio out of the dash, and disconnect the connectors at the back of the radio.

Step 10: Check all the accessories for the new Seicane car radio.

Step 11: Connect the harnesses to the back of the new Seicane car radio.

Step 12: Connect the Seicane car radio to your original car radio 's plugs.

Step 13: Put the new Seicane car radio into the dash.

Step 14: Turn on the new Seicane car radio and check whether the radio is working properly.

Step 15: Install all screws, trims, panels, bolts and the radio bezel and AC controls into their original place.

Please note:

We suggest you arrange a professional to install it. If you have any questions about installation, please send us photos about your original car's plugs, we can make a wiring diagram for your car.