

Seicane S166227 2002-2011 KIA Sorento CEED Cerato aftermarket car stereo head unit upgrade installation replacement instruction

Seicane S166227 2002-2011 KIA Sorento CEED Cerato car radio after installation



Please note:

This unit can be suitable for the following cars which are also with the same installation steps as follows.

- 2003-2009 KIA Cerato
- 2004-2010 KIA Sportage
- 2006-2009 KIA CEED
- 2002-2009 KIA Sorento
- 2003-2009 KIA Spectra
- 2005-2010 KIA Optima
- 2006-2011 KIA Rondo
- 2005-2011 KIA Rio Rio5
- 2006-2011 KIA Sedona
- 2006-2012 KIA Carens
- 2003-2009 KIA Spectra5
- 2002-2009 KIA Naza Sorento
- 2006-2010 KIA Rondo7

2005-2010 KIA Magentis
2005-2010 KIA MAGENTA
2005-2010 KIA LOTZE
2006-2010 KIA X-Trek
2004-2011 KIA Picanto
2004-2011 KIA Morning
2004-2011 KIA New Morning
2004-2011 KIA Euro Star
2004-2011 KIA Naza Suria
2004-2011 KIA Naza Picanto
2005-2011 KIA RIO JB
2005-2011 KIA New Pride
2005-2011 KIA New Pride Sedan
2005-2011 KIA New Pride
2006-2011 KIA Grand Carnival
2006-2011 KIA VQ
2006-2011 KIA Carnival Carnival R

Precautions for this installation:

1. Before you start up any work, park your car well and unplug the negative power cable to avoid any danger.
2. Please make sure that all fastened wires are isolated with electrical tape.
3. Please make sure the ignition is off to avoid short circuit.
4. Please prepare a lever and a screwdriver before the removal and the installation.
5. For your convenience, here's the recommended tools for removal and installation from Seicane, please check for more details: <http://www.seicane.com/car-dvd-dismantling-device-srd-400>

2002-2011 KIA Sorento CEED Cerato car radio installation guide

1. Pry around the edges of the trim panel with a lever.



2. Remove the trim panel.



3. Disconnect all the connectors of the trim panel.



4. Unscrew all the screws holding the original car radio in place with a screwdriver.



5. Gently take the original car radio out of the dashboard.



6. Disconnect all connectors at the back of the original car radio.



7. Check all the accessories for the new Seicane car radio.



8. Connect the harnesses to the back of the new Seicane car radio.



9. Connect the Seicane car radio to your original car radio 's plugs.

10. Turn on the new Seicane car radio to have a careful check if everything works well. If it doesn't, please check whether all the cables are connected correctly.

11. Put the new Seicane car radio into the dash.

12. Put everything into their original place. All the installation is done.

Please note:

We suggest you arrange a professional to install it. If you have any questions about installation, please send us photos about your original car's plugs, we can make a wiring diagram for your car.