

## **Seicane S166229 1996-2012 Toyota Prado RAV4 aftermarket car stereo upgrade installation replacement instruction**

Seicane S166229 1996-2012 Toyota Prado RAV4 car radio after installation



### **Please note:**

**This unit can be suitable for the following cars which are also with the same installation steps as follows.**

2001-2008 Toyota RAV4  
2004-2006 Toyota Corolla  
2003-2010 Toyota Vios  
2001-2010 Toyota Hilux  
2006-2010 Toyota Terios  
2003-2010 Toyota Land Cruiser  
2003-2010 Toyota Avanza  
2005-2010 Toyota Fortuner  
1996-2009 Toyota Prado  
2006-2012 Daihatsu Be-go  
2006-2012 Toyota Rush  
2006-2012 Daihatsu Terios Eco  
2006-2012 Daihatsu Terios Wild  
2006-2012 Perodua Nautica  
1998-2005 Toyota Echo

1998-2005 Toyota VIZI  
1998-2005 Toyota Vitz  
2003-2007 Toyota Soluna Vios  
TOYOTA FJ CRUISER  
TOYOTA ALPHARD  
TOYOTA PREVIA GL  
TOYOTA HIACE  
TOYOTA IELAS  
TOYOTA INNOVA  
TOYOTA CAMRY  
TOYOTA YARIS  
TOYOTA TUNDRA  
TOYOTA HIGHLANDER  
TOYOTA CELICA  
TOYOTA MR2  
TOYOTA 4RUNNER  
TOYOTA SEQUOIA  
TOYOTA KLUGER  
Toyota Limo

**Please notice before the installation:**

1. Please apply the parking brake and remove the negative cable on the vehicle battery before the removal to ensure safety.
2. A lever and a screwdriver need to be prepared before the installation.
3. For your convenience, here's the recommended tools for removal and installation from Seicane, please check for more details:

## **1996-2012 Toyota Prado RAV4 car radio installation guide**

1. Remove two trim panels at each side of the center console and set it aside.



2.Remove the top panel and set it aside.



3.Remove 4 screws holding the unit with a Phillips screwdriver.



4.Gently take out the panel on the radio interface.



5.Take out the radio and disconnect cables at back of it.



6. Check all the accessories for the new Seicane car radio.
7. Connect the harnesses to the back of the new Seicane car radio.
8. Connect the Seicane car radio to your original car radio's plugs.
9. Put the new Seicane car radio into the dash.
10. Turn on the new Seicane car radio and have a comprehensive check if it works well.
11. Install 4 screws back to their original position.
12. Install the trim panel back to its original place.

**Attention:**

We suggest you arrange a professional to install it. If you have any questions about installation, please send us photos about your original car's plugs, we can make a wiring diagram for your car.